

# Declaration of Performance

No. 02-015-01

## BETADEKOR<sup>®</sup> SID

Unique identification code of the product-type: 02-015

Intended use / intended uses: Manufactured exterior and interior render with organic binders used for exterior and interior render systems on walls, ceilings, pillars and partitions.

Producer: STOMIX, spol. s r. o.  
Skorošice 197  
790 65 Skorošice  
Czech Republic

System / POSV systems: System 4

Harmonised standard: EN 15824:2009  
Specifications for external renders and internal plasters based on organic binders

Notified body / notified bodies: -

Declared property / declared properties:

Essential characteristics	Performance	Harmonised technical specification
Water vapor permeability	V <sub>1</sub>	EN 15824:2009
Water absorption	W <sub>3</sub>	EN 15824:2009
Adhesion to concrete	0.3 MPa	EN 15824:2009
Durability	NPD	EN 15824:2009
Thermal conductivity	$\lambda = 0.8 \text{ W/(m.K)}$	EN 15824:2009
Reaction to fire	Euroclass C (consumption to 3.5 kg/m <sup>2</sup> )	EN 15824:2009
	Euroclass F (consumption to 3.5 kg/m <sup>2</sup> )	EN 15824:2009

Qualities of the above product are in conformity with a set of declared qualities. The Declaration of Performance is issued under the sole responsibility of the manufacturer specified above in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Skorošice, 20.5.2015



STOMIX, spol. s r. o.  
790 65 Skorošice 197

  
Libuše Zichová, Quality Manager and EMS

	STOMIX, spol. s r. o. 790 65 Skorošice 197 Czech Republic ID: 48400874	
	11	02-015-01
EN 15824:2009 Specifications for external renders and internal plasters based on organic binders		
Water vapor permeability: $V_1$ Water absorption: $W_3$ Adhesion to concrete: 0.3 MPa Durability: NPD Thermal conductivity: $\lambda = 0.8 \text{ W/(m.K)}$ Reaction to fire: Euroclass C (consumption to 3.5 kg/m <sup>2</sup> ) Euroclass F (consumption to 3.5 kg/m <sup>2</sup> )		



WWW link